

Luminaire

Code 5183-AB-N
Name Dolt Projetor 7W 600LM 4000K 36°

Measurement


Code 451/2019
Name Dolt Projetor 7W 600LM 4000K 36°

Luminaire Flux	600.55 lm	Luminaire Power	7.20 W	Efficacy	83.41 lm/W	Efficiency	100.00%
Sources Flux	600.55 lm	Maximum value	1042.49 cd	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	37 mm	Width	84 mm	Height	1 mm
Rectangular Luminous Area		Length	37 mm	Width	84 mm	Height	0 mm
Horizontal Luminous Area		0.003108 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000752 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-06-2019		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		600.55 lm	
Operator				Rated Voltage			
Temperature		25.00 °C		Rated Current			
Humidity		60.00 %		Photocell			
Notes							

Luminaire Sources

Line	Code	Name	Flux [lm]	Pow. [W]	Q.ty
	5183-AB-N	LED 7W 600LM 4000K IRC>90 SDMC<3 NICH	600.55	7.20	1
C.I.E.	97 100 100 100 100	D DIN 5040	A60		
F UTE	1.00 A	B NBN	BZ 1		

37mm x 84mm




C Halfplanes

180.0 — 0.0

ULOR 0.00 %

DLOR 100.00 %

RN 0.00 %



Luminaire

Code 5183-AB-N
Name Dolt Projetor 7W 600LM 4000K 36°

Measurem.

Code 451/2019
Name Dolt Projetor 7W 600LM 4000K 36°

Luminaire Flux	600.55 lm	Luminaire Power	7.20 W	Efficacy	83.41 lm/W	Efficiency	100.00%
Sources Flux	600.55 lm	Maximum value	1042.49 cd	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Luminous Intensity Table cd Table 1/1

	C	0.00
G 0.0		1042.49
G 5.0		1041.41
G 10.0		949.25
G 15.0		783.36
G 20.0		580.61
G 25.0		377.86
G 30.0		230.40
G 35.0		129.02
G 40.0		64.51
G 45.0		27.65
G 50.0		9.22
G 55.0		0.00
G 60.0		0.00
G 65.0		0.00
G 70.0		0.00
G 75.0		0.00
G 80.0		0.00
G 85.0		0.00
G 90.0		0.00